
# Temporal integration in rapidly presented natural scenes

Jan Drewes Weina Zhu David Melcher

62

Center for Mind/Brain Sciences, Trento University mail@jandrewes.de



### **Introduction and Methods**

The human visual system has the capability to extract information about scene context and contained objects at blazing speeds. It is an open question whether rapid categorization primarily involves **feed-forward** processes or whether **feedback** loops also contribute [1,2,3]. We employed an RSVP paradigm to probe the temporal dynamics of visual object discrimination.


To test the temporal integration of information for rapid categorization, three classes of images were prepared for the experiment. The "neutral" class contained many types of natural scenes, but did not contain any objects from either of the two target object categories. The target object categories were natural scenes containing either animals or vehicles, but not both.

We presented a rapid stream of "neutral" images at a presentation rate of 50Hz. Randomly embedded in this image sequence were either one ore two presentations of one image from one of the target object categories, adapted in contrast to each subject to achieve 57% object classification accuracy for single presentations.

The **ISI between presentations** was systematically varied from **0 to 600ms** to measure the temporal integration window.

Additionally, the background of the screen flashed at a random time (FOA), with the intention to induce a phase reset in the visual system.

Max






#### Results

Flash-Induced Oscillatory Dynamics (FOA) -

Trials were sorted by **distance from flash** (**FOA**, single-presentation trials only).


Fourier power spectra were computed individually per subject, then averaged.

Random permutation analysis (N=100k) revealed a **significant oscillatory** component at 10Hz.



Repeated Presentation Performance (ISI)

0 80 160 240 320 400 480 560




0 80 160 240 320 400 480 560

ISI (ms)

Trials were sorted by **distance between stimulus** presentations (ISI).

**Double-presentation trials** showed a **clear performance improvement** over single presentation trials.


The **performance of animal** trials is **significantly less** than the **performance of vehicle** trials, suggesting a **bias**.



Temporal window of integration –


80 160 240 320 400 480 560

Data was first **centered over [400..600ms]**. Groups of subjects were then randomly sampled from all (N=1000), and an exponential **decay function** was then fitted to the average of each re-sampled group. Analysis reveals a **significant difference** between animal and vehicle trials, with a 30% slower decay with the animal stimuli, suggesting that information about animals is combined over a longer temporal integration window.



## Recurrent processing

Fourier power spectra were computed per subject, then averaged, for pooled and stimulus separated target classes. Permutation analysis (N=100k) revealed a significant oscillatory component, only with the animal stimuli, at approx. **5Hz** (4.88).



# Conclusions

Classification accuracy was significantly higher in the double**presentation** condition.

Sorting trials by **FOA**, an **oscillatory pattern** emerged at **10Hz**.

Sorting trials by ISI, an oscillatory pattern emerged at 5Hz, only with the animal stimuli. Estimating the principal temporal integration window revealed 30% longer integration for animal stimuli.

Our findings indicate the presence of **recurrent processes** in visual perception. Oscillatory activity and estimated temporal integration windows suggest differential processing for animal and vehicle stimuli. These findings are consistent with suggestions that animals are special stimuli for the visual system.

This research was supported by a European Research Council (ERC) grant (grant agreement no. 313658)

1 Koivisto et al., "Recurrent Processing in V1/V2 Contributes to Categorization of Natural Scenes." J Neurosci 2011 2 Thorpe et al., "Speed of Processing in the Human Visual System." Nature 1996 3 Serre et al., "A Feedforward Architecture Accounts for Rapid Categorization." PNAS 2007